

INSTRUCTIONS FOR OIL CHANGE

For Simoniz 2700PSI Gas Pressure Washer (with Ducar 173cc Gas Engine)

Canadian Tire Product : 039-8055-2

Model Number: UG01

Tools required:

- M10 wrench (metric #10)
- Funnel
- Shop towels or rags
- Old Newspaper or cardboard
- Oil pan, or catch tray
- SAE 30 motor oil (refer to the engine service manual for oil recommendations)

Difficulty Level (1-3): 1 (Easy)



WARNING: BEFORE YOU START

Accidental starts can cause serious injury or death. Before performing repair, make sure machine is OFF and disable engine by disconnecting spark plug wire. HOT PARTS CAN CAUSE SEVERE BURNS. DO NOT TOUCH ENGINE WHILE OPERATING, OR JUST AFTER STOPPING. Work on a LEVEL and FLAT surface.

Step 1: Warm up the engine by letting it run for a minute so that the oil will flow more freely.

Step 2: Clean around the oil fill area. Use a clean rag to clean around the oil fill area.

Step 3: Prepare an oil pan or tray to catch the oil. Layer the area with old newspaper or cardboard to catch drips.

Step 4: Remove the Oil Plug to drain the oil. Re-install the Oil Plug securely.

Step 5: Remove the Dipstick and use a funnel to fill the Crankcase with new oil. Fill up to point of the filler neck: the level should be at the top line on dipstick.

Step 6: Reinstall Oil fill plug/dipstick and tighten securely.

