OIL CHANGE INSTRUCTIONS

For Simoniz S3200 Gas Pressure Washer (with Kohler engine)

Canadian Tire Product : 039-8056-0 Model Number: XG01

Tools and supplies required: M10 wrench (metric #10), Funnel, Shop towels or rags, Newspaper or cardboard, SAE 30 motor oil (refer to the engine service manual for oil recommendations) **Difficulty Level (1-3)**: 1 (Easy)




WARNING: BEFORE YOU START

Accidental starts can cause serious injury or death. Before performing repair, make sure machine is OFF and disable engine by disconnecting spark plug wire. HOT PARTS CAN CAUSE SEVERE BURNS. DO NOT TOUCH ENGINE WHILE OPERATING, OR JUST AFTER STOPPING. Work on a LEVEL and FLAT surface.




STEP 1: Let engine run for one minute so that the oil will warm and flow more freely.



STEP 2: Use a rag to clean around oil fill area. Prepare an oil pan to catch the oil. Layer the work area with newspaper or cardboard to catch any spills.



STEP 4: Using a wrench, remove the oil drain plug and allow oil to drain. After drainage, return the oil drain plug and tighten.



STEP 5: Remove the dipstick. Use a funnel to fill the crankcase with new oil up to the filler neck. Oil level should be at top of indicator on dipstick. Reinstall Oil fill plug/dipstick and tighten securely.