

INSTRUCTIONS FOR REPLACING SPARK PLUG

For Simoniz 2700PSI Gas Pressure Washer (with Ducar 173cc Gas Engine)

Canadian Tire Product : 039-8055-2

Model Number: UG01

Tools required: Spark Plug wrench (included with machine)

Part Number: [UG01-100-0004 \(Spark Plug\)](#) To order, see below contact details.

Difficulty Level (1-3): 1 (Easy)



WARNING: BEFORE YOU START

Accidental starts can cause serious injury or death. Before performing repair, make sure machine is OFF and disable engine by disconnecting spark plug wire. HOT PARTS CAN CAUSE SEVERE BURNS. DO NOT TOUCH ENGINE WHILE OPERATING, OR JUST AFTER STOPPING. Work on a LEVEL and FLAT surface.



STEP 1: Clean out the area around the spark plug before removal to prevent impurities from falling inside the engine.

STEP 2: Firmly grab the spark plug boot and pull it off.

STEP 3: Use the spark plug wrench to remove the spark plug.

STEP 4: Insert the new spark plug by hand. Carefully thread the spark plug into the engine by hand, turning clockwise. Manually thread the spark plug into the engine by turning clockwise at least 2 FULL TURNS.



STEP 5: Use the spark plug wrench and continue tightening turning CLOCKWISE until it stops. Do not over-tighten or you may crack the porcelain. If using a torque wrench, torque between 12 to 15 lbs. See Figure 3.